Description

Green dyed PVC film with a matt surface

Release Paper

Silicone coated paper on one side, 137 g/m², which provides excellent weed-stripping properties.

Adhesive

Polyacrylate, removable

Area of use

Developed for use on cutting plotter systems for a broad range of sandblasting applications, e.g. onto glass, plastics and wood.

Technical Data

ron
nm
min. 19 MPa min. 19 MPa
min. 130% min. 150%
(

Note

Surfaces to which the material will be applied must be thoroughly cleaned and free from dust, grease or any other contamination that could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure. The compatibility of the selected lacquers and paints should be tested by the user, prior to application of the material. Furthermore, the application information published by ORAFOL must be considered. The batch traceability according to ISO 9001 is possible on the basis of the roll number.

IMPORTANT NOTICE

All ORAMASK® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAMASK® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAMASK® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAMASK® is a registered trademark of ORAFOL Europe GmbH.

